

Single Phase Inverter with HD-Wave Technology

SE2200H, SE3000H, SE3500H, SE3680H,
SE4000H, SE5000H, SE6000H

INVERTERS



Optimized installation with HD-Wave technology

- Specifically designed to work with power optimizers
- Record-breaking efficiency
- Extremely small, lightweight and easy to install
- High reliability
- Built-in module-level monitoring
- Outdoor and indoor installation
- Fixed voltage inverter for longer strings
- Smart Energy Management control
- Advanced safety feature - integrated arc fault protection
- Compatible with the StorEdge Interface for StorEdge™ applications

/ Single Phase Inverter with HD-Wave Technology

SE2200H, SE3000H, SE3500H, SE3680H, SE4000H, SE5000H, SE6000H

	SE2200H	SE3000H	SE3500H	SE3680H	SE4000H	SE5000H	SE6000H		
OUTPUT									
Rated AC Power Output	2200	3000	3500	3680	4000	5000 ⁽¹⁾	6000	VA	
Maximum AC Power Output	2200	3000	3500	3680	4000	5000 ⁽¹⁾	6000	VA	
AC Output Voltage (Nominal)	220/230							Vac	
AC Output Voltage Range	184 - 264.5							Vac	
AC Frequency (Nominal)	50/60 ± 5							Hz	
Maximum Continuous Output Current	10	14	16	16	18.5	23	27.5	A	
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes								
INPUT									
Maximum DC Power	3400	4650	5425	5700	6200	7750 ⁽²⁾	9300	W	
Transformer-less, Ungrounded	Yes								
Maximum Input Voltage	480							Vdc	
Nominal DC Input Voltage	380							Vdc	
Maximum Input Current	6.5	9	10	10.5	11.5	13.5	16.5	Adc	
Reverse-Polarity Protection	Yes								
Ground-Fault Isolation Detection	600kΩ Sensitivity per Unit								
Maximum Inverter Efficiency	99.2							%	
European Weighted Efficiency	98.3	98.8				99		%	
Nighttime Power Consumption	< 2.5							W	
ADDITIONAL FEATURES									
Supported Communication Interfaces	RS485, Ethernet, ZigBee (optional), WiFi (optional), Cellular (optional)								
Smart Energy Management	Export Limitation, Smart Energy, StorEdge Applications								
Arc Fault Protection	Integrated, User Configurable (According to UL1699B)								
STANDARD COMPLIANCE									
Safety	IEC-62109-1/2, AS-3100								
Grid Connection Standards	AS-4777, VDE-AR-N-4105, VDE 0126-1-1, UTE C15-712, G83/2, G59/3, CEI-021, EN 50438, IEC61727, IEC62116, ÖNORM, TF3.2.1, C10-11, NRS 097-2-1								
Emissions	IEC61000-6-2, IEC61000-6-3, IEC61000-3-11, IEC61000-3-12, FCC Part 15 Class B								
INSTALLATION SPECIFICATIONS									
AC Output - Supported Cable Diameter	9-16							mm	
AC - Supported Wire Cross Section	1-13							mm ²	
DC Input	1 x MC4				2 x MC4 pair				
Dimensions (H x W x D)	280 x 370 x 142							mm	
Noise	< 25							dB(A)	
Weight	7.8				9	10.6		kg	
Cooling	Natural Convection								
Operating Temperature Range	-20 to +60 ⁽³⁾ (-40°C option)							°C	
Protection Rating	IP65 — Outdoor and Indoor								

⁽¹⁾ 4600VA in Germany

⁽²⁾ 7130VA in Germany

⁽³⁾ For power de-rating information refer to: <https://www.solaredge.com/sites/default/files/se-temperature-derating-note.pdf>